

<p>Name <b>L2440p Wide Flat Panel Monitor</b>                  Case color <b>Business black</b>                  Type-model <b>4420-HB2</b>                  Panel TFT-LCD, twisted nematic (TN), CCFL backlight                  Viewable image size <b>24.0" (610mm)</b> diagonal                  Max view area (W x H) 20.4" x 12.8" (518.4mm x 324.0mm)                  Optimum resolution <b>1920x1200</b> at 60Hz                  Maximum resolution 1920x1200 at 60Hz (205MHz max pixel rate)                  Aspect ratio 16:10                  Pixel pitch (mm) .270mm                  Dot/Pixel per Inch 94 dpi                  Brightness 300 nits or cd/m<sup>2</sup> (typical)                  Contrast ratio 1000:1 (typical)                  Pixel response time 5ms (typical)                  Color gamut 72%                  Anti-reflective Anti-reflective, anti-glare                  Vertical frequency 50 to 75Hz                  Horizontal frequency 30 to 94kHz                  Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical                  Stand Tilt, swivel, pivot, and height adjustable stand                  Bezel width <i>Sides: 0.78" (19.9mm); top: 0.78" (19.9mm); bottom: 1.12" (28.4mm)</i>                  Dimensions (HxWxD) 15.54-19.87" H x 22" W x 8.04-10.13" D;                  394.8-504.8mm H x 559.6mm W x 204.3-257.3mm D                  Power supply 35 watts typical, 50 watts maximum,                  &lt;1 watts standby/suspend, universal,                  integrated (no external brick-like power supply)                  Weight 17.84 lb; 8.09kg                  Limited warranty<sup>4</sup> <b>3 year</b> (includes backlight)                  Available date October 2008</p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 24-inch monitor</li> <li>• Supports WUXGA 1920x1200 resolution</li> <li>• High Definition (HD) ready; supports 1080p video</li> <li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Detachable rear stand cable cover and clip to hide cables</li> <li>• Carrying handle</li> <li>• 65% recycled packaging materials</li> <li>• Microsoft® Windows® Vista® Premium certified</li> </ul>
<p>VESA-compliant<sup>2</sup> VESA DDC2B/GI, VESA DPMS-compliant                  Power management ENERGY STAR® 5.0                  Ergonomics ISO 13406 Part 2<sup>1</sup>                  Pixel defect ISO 13406-2 Class II pixel defect standard                  Emission standards MPR-2, MPR-3A, FCC Class B                  Environmental TCO 03, WEEE, RoHS (EU Directive 2002/95/EC),  <b>EPEAT™ Gold rating</b>, GREENGUARD® certified</p>	 <p style="text-align: center;"><b>ThinkVision L2440p Wide Monitor</b></p>
<p>Preset resolutions                  VGA: 640x350, 640x480, 720x400                  SVGA: 800x600                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1360x768                  WXGA+: 1440x900                  UXGA: 1600x1200                  WSXGA+: 1680x1050                  WUXGA: 1920x1200                  Presets / user settings Standard presets: 27; user settings: 20</p>	
<p>Viewing adjustments <i>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</i>                  Rotating screen <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller),                  On screen display with digital user controls (8 languages)                  Control features Direct access (buttons on front) for automatic image setup                  USB hub USB 2.0 Hub (1 port into PC, 4 ports for accessories)                  Multiple input Multiple input (two different PCs attach to two different connectors; one PC shows image; select via button)                  Monitor connectors (1) VGA 15-pin D-shell, analog, blue                  (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>                  Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 2.2 meter                  (2) detachable, DVI-D at each end, digital, 2.2 meter                  Mounting features Wall or desk mounting using the Radial Arm<sup>9</sup> or third-party accessories meeting the VESA FPMPI® (100mm mount)                  Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)                  Ship group Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 2.2 meter analog signal cable, 2.2 meter digital signal cable, 2.2 meter USB cable, 1.8 meter black power cord</p>	

<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>3 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>International Warranty Service<sup>5</sup></b></li> <li>⇒ <b>Rapid Replacement Service at 1-800-426-7378</b></li> <li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>Service upgrade options:<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9234)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> </li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>ThinkVision Soundbar</td> <td style="text-align: right;">45K1263</td> </tr> <tr> <td>Kensington® Cable Lock from Lenovo</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> <tr> <td>ThinkPad Convertible Monitor Stand</td> <td style="text-align: right;">40Y7620</td> </tr> <tr> <td>ThinkVision TFT Radial Arm<sup>9</sup></td> <td style="text-align: right;">19K4464</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	ThinkVision Soundbar	45K1263	Kensington® Cable Lock from Lenovo	73P2582	Kensington Twin Head Cable Lock	45K1620	ThinkPad Convertible Monitor Stand	40Y7620	ThinkVision TFT Radial Arm <sup>9</sup>	19K4464
ThinkVision Soundbar	45K1263										
Kensington® Cable Lock from Lenovo	73P2582										
Kensington Twin Head Cable Lock	45K1620										
ThinkPad Convertible Monitor Stand	40Y7620										
ThinkVision TFT Radial Arm <sup>9</sup>	19K4464										

See footnotes for important warranty information  
 US model announced September 17, 2008